

K7GFG0507A

GAS FRYER DOUBLE TANK 7+7 It. CONTROL BOARD ON TOP - PERFORMANCE LINE



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Oil heating achieved through **optimized combustion stainless steel burners** equipped with a heat exchanger in the tank. Powerful and quick intervention of the heating elements to prevent the temperature from dropping when the product is poured into the tank.

Two tanks of 7 liters each, equipped with 8-position mechanical thermostatic valve corresponding to 8 temperature levels from 120°C to 190°C. Safety guaranteed by a thermocouple kept active by the pilot burner flame. Additional safety thermostat. Stainless steel tanks with rounded edges sloping towards the drain hole connected to a stainless steel container to collect the oil. Oil drains from the tank via a tap into an internal collection container with a filter.

Standard provided with steel baskets coated with a layer of protective material and stainless steel basin cover. **Standard provided** with one stainless steel oil container with filter.

Moulded AISI 304 stainless steel worktop for easy cleaning. Front panel in AISI 304 stainless steel. Cold-formed stainless steel tanks. Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Tested with natural gas or LPG, according to the user's needs.

Height-adjustable stainless steel legs.

Accessories available on demand.









TECHNICAL SPECIFICATIONS

Width: 400 mm Depth: 700 mm Height: 850 mm Weight: 53 kg Volume: 0.45 m³ Gas power: 11.50 kW





