

K7GFG0515

GAS FRYER SINGLE TANK 15 LT. - PERFORMANCE LINE



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Oil heating achieved through **optimized combustion stainless steel burners** equipped with a heat exchanger in the tank. Powerful and quick intervention of the heating elements to prevent the temperature from dropping when the product is poured into the tank.

One tank of 15 liters, equipped with 8-position mechanical thermostatic valve corresponding to 8 temperature levels **from 120°C to 190°C**. Safety guaranteed by a thermocouple kept active by the pilot burner flame. Additional safety thermostat.

Stainless steel tank with rounded edges sloping towards the drain hole connected to a stainless steel container to collect the oil.

Oil drains from the tank via a tap into an internal collection container with a filter.

Standard provided with steel baskets coated with a layer of protective material and stainless steel basin cover.

Standard provided with one stainless steel oil container with filter.

Moulded AISI 304 stainless steel worktop for easy cleaning. Front panel in AISI 304 stainless steel. Cold-formed stainless steel tank.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Tested with natural gas or LPG, according to the user's needs.

Height-adjustable stainless steel legs.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 400 mm
Depth: 700 mm
Height: 850 mm
Weight: 50 kg
Volume: 0.45 m³
Gas power: 15.00 kW

