

K7GPD1005

GAS BOILING PAN DIRECTLY HEATED 55 LT.



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges. Moulded, balanced stainless steel lid.

Direct heating obtained through **high efficiency stainless steel tubular burners**. Safety ensured by a thermocouple kept active by the pilot burner flame. Ignition by piezoelectric and pilot flame.

Cooking tank with AISI 316 bottom for handling particularly acid products, and AISI 304 side panels. Thermal insulation guaranteed by thick fiberglass panels. Work surface attached to the cooking tank by continuous welding.

Cooking tank capacity of 55 litres.

AISI 304 moulded stainless steel worktop with rounded edges for easy cleaning. Stainless steel front panel.

Water inlet into the tank via tap (hot/cold water) and adjustable spout. Tub drain hole with removable filter. Chrome-plated brass 2" front drain tap with insulating handle.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Tested with natural gas or LPG, according to the user's needs.

Height-adjustable stainless steel legs.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 800 mm
Depth: 700 mm
Height: 850 mm
Weight: 72 kg
Volume: 0.92 m³
Gas power: 15.50 kW

